



THE SOLARIUM 5600 ALPHA EXTRASUN+

With its clear dynamic proportions and refined details, the KBL 5600 alpha offers everything you can expect from a top class device – great variety at a competitive price.



5600 ALPHA EXTRASUN+





TECHNICAL DATA

Easy Control	



Motion

-0

Sound

System

Air Condition









Nega Voice



Aqua Cool



Aromo



Canopy:

Bench: Power consumption: Weight: Bench pane:

24 x pureSunlight lamps (~ 70,87") 2 x extraSunlight lamps (~70,87") 16 x pureSunlight lamps (~ 74,80 ") 12.1 kW \sim 1252 lbs (with air conditioning) 330 lbs (max. load capacity)



Power connection: Protective class: Mains voltage: Wire cross section: Circuit breaker recommended: 3-phase: 3 x 40 A

rear side left IP20 3-phase: 3 x 220 V / ~ / 60 Hz 3-phase: 4 x AWG8 All tanning devices with Class-A ground fault circuit interrupter GFCI.

CENTRAL EXHAUST AIR DISCHARGE

Minimum exhaust air flow rate: 594400 gal/hour Exhaust-air hose:

Exhaust-air socket ~11.81 inch High to top ~70.8 inch (with and without hot air recirculation) Ø~11.81 inch

DIMENSIONS

Fan:

Recommended roomsize: Dimensions in inch (HxWxD):

8' x 9' ~58.27" x ~91.74" x ~63.39" (closed) ~70.87" x ~91.74" x ~56.70" (open)





