



10
MINUTES

FAVORITE SOLARIUM 6800 ALPHA EXTRASUN+

The 6800 alpha extraSun+ intelligent features convince customers everywhere. Elegant design, perfect ergonomics, patented technology and individual settings ensure your favorite tan with only one click.

6800 ALPHA EXTRASUN+



Lamps



Glass Facial System



preSelection



X-Tra Tan



Easy Control



Color Motion



Bluetooth



Sound System



Mega Voice



Air Condition



Aqua Cool



Aroma



CPI

TECHNICAL DATA

Canopy:	20 x pureSunlight lamps (~ 70,87") 6 x extraSunlight lamps (~ 70,87")	200 W
Bench:	20 x pureSunlight lamps (~ 74,80 ")	
Power consumption:	14,2 kW	
Weight:	~1519 lbs (with air conditioning)	
Bench pane:	330 lbs (max. load capacity)	

ELECTRICAL REQUIREMENTS



Power connection:	rear side left
Protective class:	IP20
Mains voltage:	3-phase: 3 x 220 V / ~ / 60 Hz
Wire cross section:	3-phase: 4 x AWG6
Circuit breaker recommended:	3-phase: 3 x 50 A
All tanning devices with Class-A ground fault circuit interrupter GFCI.	

CENTRAL EXHAUST AIR DISCHARGE

Fan:	Exhaust-air socket ~11.81 inch High to top ~82.48 inch
Minimum exhaust air flow rate:	594400 gal/hour
Exhaust-air hose:	Ø ~11.81 inch

DIMENSIONS

Recommended roomsize:	9' x 10'
Dimensions in inch (HxWxD):	~60.39" x ~93.86" x ~56.34" (closed) ~76.46" x ~93.86" x ~56.34" (open)



Contraindication: This product is contraindicated for use on persons under the age of 18 years. "Contraindication: This product must not be used if skin lesions or open wounds are present." "Warning: This product should not be used on individuals who have had skin cancer or have a family history of skin cancer." "Warning: Persons repeatedly exposed to UV radiation should be regularly evaluated for skin cancer." © Copyright 2022 KBL GmbH, Germany. Errors and omissions possible. KBL GmbH reserves the right to change technical data without notice.



10
MINUTES

THE SOLARIUM 6700 ALPHA

The 6700 alpha provides the maximum of technology, comfort and first class at an unbeatable price-performance ratio. This is luxury at a price made for starters!

6700 ALPHA



Lamps



Glass Facial System



X-Tra Tan



Easy Control



Color Motion



Bluetooth



Sound System



Mega Voice



Air Condition



Aqua Cool



Aroma



EP

TECHNICAL DATA

Canopy:	26 x pureSunlight lamps (~ 70,87")	160 W
Bench:	20 x pureSunlight lamps (~ 74,80 ")	180 W
Power consumption:	11,7 kW	
Weight:	~1519 lbs (with air conditioning)	
Bench pane:	330 lbs (max. load capacity)	

ELECTRICAL REQUIREMENTS



Power connection:	rear side left
Protective class:	IP20
Mains voltage:	3-phase: 3 x 220 V / ~ / 60 Hz
Wire cross section:	3-phase: 4 x AWG6
Circuit breaker recommended:	3-phase: 3 x 50 A
	All tanning devices with Class-A ground fault circuit interrupter GFCI.

CENTRAL EXHAUST AIR DISCHARGE

Fan:	Exhaust-air socket ~11.81 inch
	High to top ~82.48 inch
Minimum exhaust air flow rate:	594400 gal/hour
Exhaust-air hose:	Ø ~11.81 inch

DIMENSIONS

Recommended roomsize:	9' x 10'
Dimensions in inch (HxWxD):	~60.39" x ~93.86" x ~56.34" (closed)
	~76.46" x ~93.86" x ~56.34" (open)



Contraindication: This product is contraindicated for use on persons under the age of 18 years. "Contraindication: This product must not be used if skin lesions or open wounds are present." "Warning: This product should not be used on individuals who have had skin cancer or have a family history of skin cancer." "Warning: Persons repeatedly exposed to UV radiation should be regularly evaluated for skin cancer." © Copyright 2022 KBL GmbH, Germany. Errors and omissions possible. KBL GmbH reserves the right to change technical data without notice.