



THE HIGH-END SOLARIUM 7900 ALPHA EXTRASUN+

The KBL 7900 caters to the individual style of each tanning salon. Fully-loaded with comfort and performance features this solarium will be a great addition to your line-up.



7900 ALPHA EXTRASUN+



Glass Facial System





X-Tra Ta

Beauty Booster HyperRed



Easy

Control

preSelection





Color Motion







Ααυα Coo













Aroma



Canopy:

Bench: Power consumption: Weight: Bench pane:

20 x pureSunlight lamps (~ 70,87") 6 x extraSunlight lamps (~70,87") 24 x pureSunlight lamps (~ 74,80 ") 14.9 kW \sim 1552 lbs (with air conditioning)



330 lbs (max. load capacity)

ELECTRICAL REQUIREMENTS

Power connection: Protective class: Mains voltage: Wire cross section: Circuit breaker recommended: 3-phase: 3 x 50 A

rear side left IP20 3-phase: 3 x 220 V / \sim / 60 Hz 3-phase: 4 x AWG6 All tanning devices with Class-A ground fault circuit interrupter GFCI.

CENTRAL EXHAUST AIR DISCHARGE

Minimum exhaust air flow rate: 594400 gal/hour

Exhaust-air hose:

Exhaust-air socket ~11.81 inch High to top ~82.48 inch Ø~11.81 inch

DIMENSIONS

Fan:

Recommended roomsize: Dimensions in inch (HxWxD): 9' x 10' ~67.44" x ~93.86" x ~56.34" (closed) ~82.16" x ~93.86" x ~56.34" (open)







