

# OUT WITH THE OLD AND IN WITH THE NEW

—Hybrid—  
SUN



---

## TOWER HYBRIDSUN

The KBL Tower hybridSun combines pureSunlight and smartSunlight for an especially satisfying tanning result. A great performing stand-up with a compact footprint.



# TECHNICAL DATA – TOWER HYBRIDSUN



Light Select



Easy Control



Body Fan



Sound System



Mega Voice



Bluetooth

26 x pureSunlight lamps (180W)  
26 x smartSunlight lamps (180W)

Power consumption: 10 kW

Weight: ~860 lbs

Floor plate: 330 lbs (max. load capacity)

## ELECTRICAL REQUIREMENTS

Power connection: rear side left

Protective class: IP20

Mains voltage: 3-phase: 3 x 220 V / ~ / 60 Hz

Wire cross section: 3-phase: 4 x AWG8

Circuit breaker recommended: 3-phase: 3 x 40 A

All tanning devices with Class-A ground fault circuit interrupter GFCI.

## CENTRAL EXHAUST AIR DISCHARGE

Fan: Exhaust-air socket  $\varnothing$  ~11.81 inch

Minimum exhaust air flow rate: 528344 gal/hour

Exhaust-air hose:  $\varnothing$  ~11.81 inch

## DIMENSIONS

Recommended roomsize: 7' x 7'

Dimensions in inch (HxWxD): 85.83 x 55.12 x 55.31 (closed)

85.83 x 55.12 x 77.28 (opened)

