



10
MINUTES

**THE TOWER
PURE ENERGY 5.0**

The KBL Tower pureEnergy 5.0 offers a combination of unprecedented, exclusive characteristics. Ultimate tanning results by maximum power for users and reduced energy consumption and heat development.

TOWER PURE ENERGY 5.0



Lamps



Easy Control



Color Motion



Body Cool



Bluetooth



Sound System



Mega Voice



VibraNano*

TECHNICAL DATA

Lamps:	52 x pureSunlight lamps (~78,74") 200 W
Power consumption:	9,1 kW
Weight:	~777 lbs without central exhaust-air module ~864 lbs with central exhaust-air module
Floor plate:	330 lbs (max. load capacity)

ELECTRICAL REQUIREMENTS



Power connection:	rear side left
Protective class:	IP20
Mains voltage:	3-phase: 3 x 220 V / ~ / 60 Hz
Wire cross section:	3-phase: 4 x AWG8
Circuit breaker recommended:	3-phase: 3 x 40 A
	All tanning devices with Class-A ground fault circuit interrupter GFCI.

CENTRAL EXHAUST AIR DISCHARGE

Fan:	Exhaust-air socket ~11.81 inch
Minimum exhaust air flow rate:	528344 gal/hour
Exhaust-air hose:	Ø ~11.81 inch

DIMENSIONS

Recommended roomsize:	7' x 7'
Dimensions in inch (HxWxD):	~93.23" x ~54.93" x ~48.55" (closed)
	With central exhaust-air module -> depth plus 13.07
	~93.23" x ~54.93" x ~72.56" (open)



Contraindication: This product is contraindicated for use on persons under the age of 18 years. "Contraindication: This product must not be used if skin lesions or open wounds are present." "Warning: This product should not be used on individuals who have had skin cancer or have a family history of skin cancer." "Warning: Persons repeatedly exposed to UV radiation should be regularly evaluated for skin cancer." © Copyright 2022 KBL GmbH, Germany. Errors and omissions possible. KBL GmbH reserves the right to change technical data without notice.